



# MG25P12P3

---

## IGBT Modules

V <sub>CE(S)</sub>	1200V
I <sub>C</sub>	25A

## Applications

- Motor Drivers
- AC and DC servo drive amplifier
- UPS (Uninterruptible Power Supplies)

## Features

- Low switching losses
- Low  $V_{ce(sat)}$  with positive temperature coefficient
- Including fast & soft recovery anti-parallel FWD
- Low inductance case
- High short circuit capability(10us)
- Isolated heatsink using DBC technology
- Maximum junction temperature 175

## ● IGBT-



# MG25P12P3

## ● IGBT- inverter

### Characteristic values

Parameter	Symbol	Conditions	Value			Unit
			Min.	Typ.	Max.	
	$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C=1.2mA, T_{vj}=25^{\circ}C$	5.2	5.8	6.4	V
Collector-Emitter Cut-off Current	$I_{CES}$	$V_{CE}=1200V, V_{GE}=0V, T_{vj}=25$			1.0	mA



# MG25P12P3

## ● Diode-inverter

### Absolute Maximum Ratings

Parameter	Symbol	Conditions	Value	Unit
Repetitive Peak Reverse Voltage	$V_{RRM}$	$T_{vj}=25^{\circ}\text{C}$	1200	V
Continuous DC Forward Current	$I_F$		25	A
Repetitive Peak Forward Current	$I_{FRM}$	$t_p=1\text{ms}$	50	A
$I^2t$ -value	$I^2t$	$V_R=0, t_p=10\text{ms}, T_{vj}=125^{\circ}\text{C}$	90.0	A <sup>2</sup> s
		$V_R=0, t_p=10\text{ms}, T_{vj}=150^{\circ}\text{C}$	75.0	

### Characteristic values

Parameter	Symbol	Conditions	Value	Unit
			Min.	
Forward Voltage				

Forward Voltage



# MG25P12P3

## ● IGBT-brake-chopper

### Absolute Maximum Ratings

Parameter	Symbol	Conditions	Value
Collector-Emitter Voltage	$V_{CES}$	$V_{GE}=0V, I_C=1mA, T_{vj}=25^\circ C$	1200
Continuous Collector Current	$I_C$	$T_C=100^\circ C, T_{vjmax}=175^\circ C$	25
Repetitive Peak Collector Current	$I_{CRM}$	$t_p=1ms$	50
Gate-Emitter Voltage	$V_{GES}$	$T_{vj}=25^\circ C$	$\pm 20$
Total Power Dissipation	$P_{tot}$	$T_C=25^\circ C, T_{vjmax}=175^\circ C$	175

### Characteristic values

Parameter	Symbol	Conditions	Value		
			Min.	Typ.	Max.
Gate-emitter Threshold Voltage	$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C=1.2mA, T_{vj}=25^\circ C$	5.2	5.8	
Collector-Emitter Cut-off Current	$I_{CES}$	$V_{CE}=1200V, V_{GE}=0V, T_{vj}=25$			
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=25A, V_{GE}=15V, T_{vj}=25^\circ C$		1.85	
		$I_C=25A, V_{GE}=15V, T_{vj}=125^\circ C$		2.15	
		$I_C=25A, V_{GE}=15V, T_{vj}=150^\circ C$		2.25	
Gate Charge	$Q_G$			0.20	
Input Capacitance	$C_{ies}$	$V_{CE}=25V, V_{GE}=0V, f=1MHz, T_{vj}=25$		1.90	
Reverse Transfer Capacitance	$C_{res}$			0.10	
Gate-Emitter leakage current	$I_{GES}$	$V_{CE}=0V, V_{GE}=20V, T_{vj}=25^\circ C$			



# MG25P12P3

Turn-on Delay Time	$t_{d(on)}$	$I_C = 25\text{ A}$ $V_{CE} = 600\text{ V}$ $V_{GE} = \pm 15\text{ V}$ $R_G = 20\Omega$ $T_{vj} = 125^\circ\text{C}$	28	ns
Rise Time	$t_r$		21	ns
Turn-off Delay Time	$t_{d(off)}$		284	ns
Fall Time	$t_f$		212	ns
Energy Dissipation During Turn-on Time	$E_{on}$		2.4	mJ
Energy Dissipation During Turn-off Time	$E_{off}$		2.18	mJ
SC Data	$I_{sc}$		$T_p \leq 10\mu\text{s}, V_{GE} = 15\text{ V}, T_{vj} = 150^\circ\text{C},$ $V_{cc} = 900\text{ V}, V_{CEM} \leq 1200\text{ V}$	120

## ● Diode-Brake-Chopper

### Absolute Maximum Ratings

Parameter	Symbol	Conditions	Value	Unit
Repetitive Peak Reverse Voltage	$V_{RRM}$	$T_{vj} = 25^\circ\text{C}$	1200	V
Continuous DC Forward Current	$I_F$		15	A
Repetitive Peak Forward Current	$I_{FRM}$	$t_p = 1\text{ ms}$	30	A
$I^2t$ -value	$I^2t$	$V_R = 0, t_p = 10\text{ ms}, T_{vj} = 125^\circ\text{C}$	16.0	A <sup>2</sup> s
		$V_R = 0, t_p = 10\text{ ms}, T_{vj} = 150^\circ\text{C}$	14.0	

### Characteristic values

Parameter	Symbol	Conditions	Value			Unit
			Min.	Typ.	Max.	
Forward Voltage	$V_F$	$I_F = 15\text{ A}, T_{vj} = 25^\circ\text{C}$		2.00	2.65	V
		$I_F = 15\text{ A}, T_{vj} = 125^\circ\text{C}$		2.10		
		$I_F = 15\text{ A}, T_{vj} = 150^\circ\text{C}$		2.10		
Recovered Charge	$Q_{rr}$	$I_F = 15\text{ A}$		1.20		uC
Peak Reverse Recovery Current	$I_{rr}$	$V_R = 600\text{ V}$ $-di_F/dt = 600\text{ A}/\mu\text{s}$		13.0		A
Reverse Recovery Energy	$E_{rec}$	$T_{vj} = 25^\circ\text{C}$		0.37		mJ
Recovered Charge	$Q_{rr}$	$I_F = 15\text{ A}$		2.05		uC
Peak Reverse Recovery Current	$I_{rr}$	$V_R = 600\text{ V}$ $-di_F/dt = 600\text{ A}/\mu\text{s}$		12.0		A
Reverse Recovery Energy	$E_{rec}$	$T_{vj} = 125^\circ\text{C}$		0.68		mJ



# MG25P12P3

## ● Diode-Rectifier

### Absolute Maximum Ratings

Parameter	Symbol	Conditions	Value	Unit
Repetitive Peak Reverse Voltage	$V_{RRM}$	$T_j=25^{\circ}\text{C}$	1600	V
Average output Current 50/60Hz, sine wave	$I_{F(AV)}$	$T_c=100^{\circ}\text{C}$	35	A
Maximum RMS Current at Rectifier Output	$I_{RMSM}$	$T_c=100^{\circ}\text{C}$	60	A
Surge Forward Current	$I_{FSM}$	$V_R=0, t_p=10\text{ms}, T_j=45^{\circ}\text{C}$	320	A
$I^2t$ -value	$I^2t$	$V_R=0, t_p=10\text{ms}, T_j=45^{\circ}\text{C}$	510	$\text{A}^2\text{s}$

### Characteristic values

Parameter	Symbol	Conditions	Value			Unit
			Min.	Typ.	Max.	
Diode Forward Voltage	$V_F$	$I_F=10\text{A}, T_j=150^{\circ}\text{C}$		1.02		V
Reverse Current	$I_R$	$T_j=150^{\circ}\text{C}, V_R=1600\text{V}$			2	mA

## ● NTC-Thermistor

### Characteristic values

Parameter	Symbol	Conditions	Value			Unit
			Min.	Typ.	Max.	
Rated Resistance	$R_{25}$			5.0		$\text{k}\Omega$
Deviation of R100	R/R	$T_c=100, R_{100}=493.3\Omega$	-5		5	%
Power Dissipation	$P_{25}$				20.0	mW
B-value	$B_{25/50}$	$R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298.15\text{K}))]$		3375		K



# MG25P12P3



## ● Module Characteristics

$T_C=25^{\circ}\text{C}$  unless otherwise specified

Parameter	Symbol	Conditions	Value			Unit
			Min.	Typ.	Max.	
Isolation voltage	$V_{\text{isol}}$	$t=1\text{min}, f=50\text{Hz}$	2500			V
Maximum Junction Temperature	$T_{\text{jmax}}$				175	$^{\circ}\text{C}$
Operating Junction Temperature	$T_{\text{vj op}}$		-40		150	$^{\circ}\text{C}$
Storage Temperature	$T_{\text{stg}}$		-40		125	$^{\circ}\text{C}$
Stray-inductance-module	$L_{\text{SCE}}$			30		nH
Module lead resistance, terminals-chip	$R_{\text{CC}'+\text{EE}'}$	$T_C=25^{\circ}\text{C}$ , per switch		5.00		m $\Omega$
	$R_{\text{AA}'+\text{CC}'}$			6.00		
Thermal Resistance Junction-to Case	$R_{\theta \text{JC}}$	per IGBT-inverter		0.75	0.85	K/W
		per Diode-inverter		1.10	1.20	
		per IGBT-brake-copper		0.75	0.85	
		per Diode-chopper		1.30	1.45	
		per Diode-rectifier		0.90	1.25	
Thermal Resistance Case-to Sink	$R_{\theta \text{CS}}$	per IGBT-inverter		0.70		K/W
		per Diode-inverter		0.90		
		per IGBT-brake-copper		0.70		
		per Diode-chopper		1.05		
		per Diode-rectifier		0.95		
		per Module		0.037		
Mounting Force Per Clamp	F		30		80	N
Weight of Module	G			45		g







# MG25P12P3











# MG25P12P3





# MG25P12P3






# MG25P12P3

---




# MG25P12P3

## Circuit Diagram



## ● Package Dimensions

