



Pin Configuration



SOP-7

Marking information



SOP-7

DP2701X for product name:

DP2701X represents the date (month/year), and XXXXXX represents the batch code. The first and fourth X on behalf of the date, such as 10/15, represents the month and year, respectively. The second and third X, represents the first year, and the fifth and sixth X, represents the last year of the date.

Typical Output Power Table(1)

Output Voltage (V _O)	Output Current (I _O)	Power	
		P _{out} (W)	P _{in} (W)
5.0	1.0	5.0	5.5
5.0	2.0	10.0	11.0
5.0	3.0	15.0	16.5
5.0	4.0	20.0	22.0
5.0	5.0	25.0	27.5
5.0	6.0	30.0	33.0
5.0	7.0	35.0	38.5
5.0	8.0	40.0	44.0
5.0	9.0	45.0	49.5
5.0	10.0	50.0	55.0
5.0	11.0	55.0	60.5
5.0	12.0	60.0	66.0
5.0	13.0	65.0	71.5
5.0	14.0	70.0	77.0
5.0	15.0	75.0	82.5
5.0	16.0	80.0	88.0
5.0	17.0	85.0	93.5
5.0	18.0	90.0	99.0
5.0	19.0	95.0	104.5
5.0	20.0	100.0	110.0
5.0	21.0	105.0	115.5
5.0	22.0	110.0	121.0
5.0	23.0	115.0	126.5
5.0	24.0	120.0	132.0
5.0	25.0	125.0	137.5
5.0	26.0	130.0	143.0
5.0	27.0	135.0	148.5
5.0	28.0	140.0	154.0
5.0	29.0	145.0	159.5
5.0	30.0	150.0	165.0
5.0	31.0	155.0	170.5
5.0	32.0	160.0	176.0
5.0	33.0	165.0	181.5
5.0	34.0	170.0	187.0
5.0	35.0	175.0	192.5
5.0	36.0	180.0	198.0
5.0	37.0	185.0	203.5
5.0	38.0	190.0	209.0
5.0	39.0	195.0	214.5
5.0	40.0	200.0	220.0
5.0	41.0	205.0	225.5
5.0	42.0	210.0	231.0
5.0	43.0	215.0	236.5
5.0	44.0	220.0	242.0
5.0	45.0	225.0	247.5
5.0	46.0	230.0	253.0
5.0	47.0	235.0	258.5
5.0	48.0	240.0	264.0
5.0	49.0	245.0	269.5
5.0	50.0	250.0	275.0
5.0	51.0	255.0	280.5
5.0	52.0	260.0	286.0
5.0	53.0	265.0	291.5
5.0	54.0	270.0	297.0
5.0	55.0	275.0	302.5
5.0	56.0	280.0	308.0
5.0	57.0	285.0	313.5
5.0	58.0	290.0	319.0
5.0	59.0	295.0	324.5
5.0	60.0	300.0	330.0
5.0	61.0	305.0	335.5
5.0	62.0	310.0	341.0
5.0	63.0	315.0	346.5
5.0	64.0	320.0	352.0
5.0	65.0	325.0	357.5
5.0	66.0	330.0	363.0
5.0	67.0	335.0	368.5
5.0	68.0	340.0	374.0
5.0	69.0	345.0	379.5
5.0	70.0	350.0	385.0
5.0	71.0	355.0	390.5
5.0	72.0	360.0	396.0
5.0	73.0	365.0	401.5
5.0	74.0	370.0	407.0
5.0	75.0	375.0	412.5
5.0	76.0	380.0	418.0
5.0	77.0	385.0	423.5
5.0	78.0	390.0	429.0
5.0	79.0	395.0	434.5
5.0	80.0	400.0	440.0
5.0	81.0	405.0	445.5
5.0	82.0	410.0	451.0
5.0	83.0	415.0	456.5
5.0	84.0	420.0	462.0
5.0	85.0	425.0	467.5
5.0	86.0	430.0	473.0
5.0	87.0	435.0	478.5
5.0	88.0	440.0	484.0
5.0	89.0	445.0	489.5
5.0	90.0	450.0	495.0
5.0	91.0	455.0	500.5
5.0	92.0	460.0	506.0
5.0	93.0	465.0	511.5
5.0	94.0	470.0	517.0
5.0	95.0	475.0	522.5
5.0	96.0	480.0	528.0
5.0	97.0	485.0	533.5
5.0	98.0	490.0	539.0
5.0	99.0	495.0	544.5
5.0	100.0	500.0	550.0

(1) Output current limited by temperature.

(2) Input 10VAC will fold back to 9VAC.

(3) Start with cold conditions, output **continuous power in a non-ventilated enclosed adapter with sufficient drain pattern as per**

